


# BLOCK 3 RECESSED


## 6.3W DOWNLIGHT LUMINAIRE



- Compact, linear, stylish construction
- Supplied with non-dimmable LED driver
- 123 lm/W module
- Colour rendering index: 85
- Colour temperature options: 2700K, 3000K, 4000K, 5000K
- Beam pattern options: 12°, 34°, 48°
- 3 steps MacAdam ellipse binning
- Uniform and comfort light
- IP20
- Dimension: 102 x 60 x 32.5mm

*The information above is at nominal values accuracy of +/-7%.*

### FIXTURE COLOUR OPTIONS



### AVAILABLE OPTIONS

#### DRIVER




(ND)

#### TEMPERATURE



#### BEAM ANGLE



### APPLICATION


- Hotel and galleries
- Offices
- Retail, fashion stores and showroom
- Residential

### TECHNOLOGY BENEFITS

- Superior light rendering quality offering balanced white with embedded green and red tone
- Excellent cost savings and quicker ROI
- Quick installation, no costly modification required
- Low maintenance
- Comfort, safety and no glass

### DIMENSIONS (MM)

*\*Displayed height measurements are for highest point of tilting.*



### SYSTEM SPECIFICATIONS

LED System Power	Colour	Beam Angle	CRI 90	
			Luminous Flux	Driver Options
6.3W	WARM : 2700K	12°	776	ND
	WARM : 3000K	34°		
	NATURAL : 4000K	48°		
	COOL : 5000K			

Data are based on 3000K. Nominal data of 2700K and 3500K are shared with 3000K.  
Higher CCT of 4000K and 5000K will have a nominal data value of 5% higher than published.

the table information is at nominal values accuracy of +/-7% nominal CRI -85, equal to Ra >80-87, R9 > 0 nominal CRI -95, equal to Ra >90-97, R9 > 50

### DETAILS SPECIFICATION

Family Type	BLOCK Series
Mains voltage	220-240V
Colour options	Matt Black, Matt White, Chrome, Copper
Installation Compatibility	BLOCK
Lifetime	50,000 HOURS (80% lumen maintenance at Ta = 25°C)
Mains connection	Screw terminal connection
Materials	Aluminium, plastic
Fire safety	Glow wire test 750°C, UL94V-0, VW-1
Flammability mark	F
IP code	IP20
Safety class	Class 2
Standards	IEC 60598-1, IEC 61347-2-13
Regulatory markings	CE, CB, RCM
Dimensions	102 x 60 x 32.5mm

FIXTURE					DRIVER
LED Power	Colour	Beam Angle	Colour Temp	CRI	Dimming
<b>BLOCK3-R</b> 6.3W	---	---	---	---	---
<b>WH</b> Matt White		<b>12</b> 12°	<b>27</b> 2700K	<b>90</b> CRI 90	<b>ND</b> Non-Dim
<b>MB</b> Matt Black		<b>34</b> 34°	<b>30</b> 3000K		
<b>CR</b> Chrome		<b>48</b> 48°	<b>40</b> 4000K		
<b>CP</b> Copper			<b>50</b> 5000K		

example: BLOCK3-R.WH.12.30.90.ND