

CUBE 4 RECESSED


9.2W DOWNLIGHT
LUMINAIRE



- Compact, linear, stylish construction
- Supplied with non-dimmable LED driver
- 64 lm/W module
- Colour rendering index: 85
- Colour temperature options: 2700K, 3000K, 4000K, 5000K
- Beam pattern options: 8°, 15°, 25°
- 3 steps MacAdam ellipse binning
- Uniform and comfort light
- IP20
- Dimension: 60 x 60 x 75mm

*The information above
is at nominal values
accuracy of +/-7%.*

FIXTURE COLOUR OPTIONS



AVAILABLE OPTIONS

DRIVER



(ND)

TEMPERATURE



BEAM ANGLE



8° 15° 25°

APPLICATION


- Hotel and galleries
- Offices
- Retail, fashion stores and showroom
- Residential

TECHNOLOGY BENEFITS

- Superior light rendering quality offering balanced white with embedded green and red tone
- Excellent cost savings and quicker ROI
- Quick installation, no costly modification required
- Low maintenance
- Comfort, safety and no glass

DIMENSIONS (MM)

**Displayed height measurements are for
highest point of tilting.*



SYSTEM SPECIFICATIONS

LED System Power	Colour	Beam Angle	CRI 85	
			Luminous Flux	Driver Options
9.2W	WARM : 2700K	8°	585	ND
	WARM : 3000K	15°		
	NATURAL : 4000K	25°		
	COOL : 5000K			

Data are based on 3000K. Nominal data of 2700K and 3500K are shared with 3000K.
Higher CCT of 4000K and 5000K will have a nominal data value of 5% higher than published.

the table information is at nominal values accuracy of +/-7% nominal CRI >85, equal to Ra >80-87, R9 > 0 nominal CRI >95, equal to Ra >90-97, R9 > 50

DETAILS SPECIFICATION

Family Type	CUBE Series
Mains voltage	220-240V
Colour options	Matt Black, Matt White, Chrome, Copper
Installation Compatibility	CUBE RECESSED
Lifetime	50,000 HOURS (80% lumen maintenance at Ta = 25°C)
Mains connection	Screw terminal connection
Materials	Aluminium, plastic
Fire safety	Glow wire test 750°C, UL94V-0, VW-1
Flammability mark	F
IP code	IP20
Safety class	Class 2
Standards	IEC 60598-1, IEC 61347-2-13
Regulatory markings	CE, CB, RCM
Dimensions	60 x 60 x 75mm

FIXTURE					DRIVER
LED Power	Colour	Beam Angle	Colour Temp	CRI	Dimming
CUBE4-R 9.2W	---	---	---	---	---
WH Matt White	8 8°	27 2700K	85 CRI 85	ND Non-Dim	
MB Matt Black	15 15°	30 3000K			
CR Chrome	25 25°	40 4000K			
CP Copper		50 5000K			

example: CUBE4-R.WH.8.30.85.ND