

20 PRO WARM DIM

6.2W DIM-TO-WARM
LED MODULE



- Feather weight construction ~44 grams
- Class 2 LED module with external LED driver
- >70 lm/W module
- Colour rendering index, ProART Ra~95
- 3 steps MacAdam ellipse binning
- ATePS™ smart thermal dimming to protect LED lifetime
- ComfyEYE aspect provides high quality uniform and comfort light with low stroboscopic optical flicker less than 5%**
- IP54



*ATEPS™ Automated Thermal Protection System is the trademark of ELR.

APPLICATION


- Hotel and galleries
- Offices
- Retail, fashion stores and showroom
- Residential

TECHNOLOGY BENEFITS


- Superior light rendering quality offering balanced white with embedded green and red tone
- Excellent cost savings and quicker ROI
- Quick installation, no costly modification required
- Low maintenance
- Comfort, safety and no glass

AVAILABLE OPTIONS



DRIVER



BEAM ANGLE




TEMPERATURE




DIMENSIONS (MM)

*Displayed height measurements are for highest point of fitting.




20 PRO WARM DIM

POLAR DIAGRAM



CONE DIAGRAM



	Emax (lx)	
	30°	
E (0°)	1045	
Cone DØ (m)	0.54	
E (0°)	281	
Cone DØ (m)	1.07	
E (0°)	116	
Cone DØ (m)	1.61	

Ø = DIAMETER

SYSTEM SPECIFICATIONS

					PROART CRI 95		
LED Lamp Power	LED System Power	Colour	CCT	Beam Angle	Intensity (cd)	Luminous Flux	Driver Options
6.2W	8W	WARM DIM	1800K ~ 2700K	30°	1040	450	PH, AN, DA

the table information is at nominal values accuracy of +/-7%
nominal CRI ~95, equal to Ra >90-97, R9 > 50

DETAILS SPECIFICATION

Family Type	20 PRO WARM DIM Series
Mains Voltage	220-240, 50Hz
Colour options	Black
Installation Compatibility	Compatible with MR11
Lifetime	50,000 HOURS (80% lumen maintenance at Ta = 25C), B10
Dimming	Phase (triac) dimmer, 0-10V, DALI
Mains connection	Loop-in-loop-out terminals for convenient connection
Materials	Aluminium, plastic
Fire safety	Glow wire test 850C, UL94V-0, VW-1
Flammability mark	F
IP Code (Module Only)	IP54
Safety class	Class 2
Standards	IEC 62031, IEC 61347-2-13
Regulatory markings	CE, CB, RCM
Weight	~ 44g

LED MODULE				DRIVER
LED Power	Beam Angle	Colour Temp	CRI	Dimming
ELR20P 6.2W	30 30°	WD WARM DIM	PA ProART	PH Phase
				AN 0-10V
				DA DALI

example: ELR20P.30.WD.PA.DA