

FM8-168


PROFESSIONAL SINGLE CCT FLEXIBLE LINEAR LED MODULE



AVAILABLE OPTIONS

CCT OPTIONS

SINGLE CCT



DRIVER DIMMING OPTIONS



ACCESSORIES




DIMENSIONS (MM)



- Width x Height : 8mm x 1.5mm (Bare Strip)
- Cut Section : 7 LEDs, 41.67mm
- LED Pitch : 5.9mm
- LEDs per Meter : 168 LEDs/m

PHOTOMETRICS






CRI	ProART (CRI~95)
SDCM	3 step MacAdam ellipse
Lifetime	Up to 50,000 hours L80 lamp life at Ta = 25°C
Voltage	24V DC
Power Options	15W/m
Light Effect	Narrow LED pitch distance for light homogeneity
Luminous Flux	Up to 1733lm/m
Efficacy	Up to 115.5lm/W
Operating Temperature	Ta (min) = -20°C, Ta (max) = +50°C
Wire Connection	Supplied with insulated AWG 20 wires at 150mm length
Ingress Protection	IP20
Beam Angle	120°

SPECIFICATIONS

CCT	Efficacy (lm/W)	Luminous Flux per meter (lm/m)									
		Default (Max.)	With CVMPS150 Dip Switch Settings *								
			On "8"	On "7"	On "6"	On "5"	On "4"	On "3"	On "2"	On "1"	
		15W/m	13.5W/m	12W/m	10.5W/m	9W/m	7.5W/m	6W/m	4.5W/m	3W/m	
2400K	94.6	1419	1277	1135	993	851	710	568	426	284	
2700K											
3000K											
3500K	110.0	1650	1485	1320	1155	990	825	660	495	330	
4000K											
5000K											
Correction Factor		1.00	0.90	0.80	0.70	0.60	0.50	0.40	0.30	0.20	



⚠ When using CVMPS150 with LED module, the driver / power supply unit capacity must be based on the maximum load of the connected LED module.

ORDERING MATRIX

Module	Power		CCT		Length		Strip Option	
FM8-168	15	15W/m	24	2400K	5M	5m Reel*	N	Bare Strip
			27	2700K			FB	Aluminium Flat Bar
			30	3000K				
			35	3500K				
			40	4000K				
			50	5000K				

Example: FM8-168-15-30-5M-N

FM8 flexible linear LED strips are supplied with insulated AWG 20 wires at 150mm length on both ends.

*Supplied in standard length of 5m per reel, customised lengths are available upon request and additional charges may apply.