

SPACE² OPAL LIGHT

12W MAGNETIC TRACK
LUMINAIRE



FIXTURE COLOUR



Matt Black

ELR[®]



- Supplied with non-dimmable or 0-10V/DALI dimmable LED driver
- >30lm/W module
- Colour rendering index: 95
- Colour temperature options: 2700K, 3000K, 4000K
- Beam pattern options: 100°
- 3 steps MacAdam ellipse binning
- Uniform and comfort light
- DC 48V
- IP20

AVAILABLE OPTIONS

DRIVER



COLOUR TEMPERATURE




BEAM ANGLE



100°

DIMENSIONS (MM)



SYSTEM SPECIFICATIONS

LED Lamp Power	LED System Power	Colour Temperature	Beam Angle	PROART CRI 95		Driver Options
				Intensity (cd)	Luminous Flux (lm)	
12W	15W	WARM : 2700K WARM : 3000K NATURAL : 4000K	100°	153	371	ND, AN, DA

Data are based on 3000K. Nominal data of 2700K and 3500K are shared with 3000K.
Higher CCT of 4000K and 5000K will have a nominal data value of 5% higher than published.

the table information is at nominal values accuracy of +/-7%
nominal CRI =95, equal to Ra >90-97, R9 > 50

DETAILS SPECIFICATION

Family Type	Space ² Series
Mains Voltage	DC 48V
Lifetime	50,000 hours (80% lumen maintenance at Ta = 25°C)
Dimming	0-10V, DALI
Mains Connection	Magnetic track
Materials	Aluminium, plastic
Fire Safety	VW-1
Flammability Mark	F
IP Code	IP20
Safety Class	Class 3
Standards	IEC 60598-1, IEC 61347-2-13
Regulatory Markings	CE, CCC, RoHS

ORDERING MATRIX CHART

FIXTURE		LED MODULE				DRIVER
Type	Colour	LED Power	Beam Angle	Colour Temp	CRI	Dimming
S-OPAL	—	—	—	—	—	—
	MB Matt Black	12 12W	100 100°	27 2700K	PA ProART	ND Non-Dim
				30 3000K		AN 0-10V
				40 4000K		DA DALI

example: S-OPAL.MB.12.100.30.PA.ND