

SPACE² PENDANT

10W MAGNETIC TRACK
LUMINAIRE



FIXTURE COLOUR



Matt Black

- Supplied with non-dimmable or 0-10V/DALI dimmable LED driver
- >80lm/W module
- Colour rendering index: 95
- Colour temperature options: 2700K, 3000K, 4000K
- Beam pattern options: 15°, 24°, 38°
- 3 steps MacAdam ellipse binning
- Uniform and comfort light
- DC 48V
- IP20

AVAILABLE OPTIONS

DRIVER



(ND)



(AN)



(DA)

COLOUR TEMPERATURE



2700K


3000K

4000K



ProART

BEAM ANGLE



15° 24° 38°

ACCESSORIES




Honeycomb
Anti-Glare Louvre



Soft Lens

DIMENSIONS (MM)



SYSTEM SPECIFICATIONS

				PROART CRI 95		
LED Lamp Power	LED System Power	Colour Temperature	Beam Angle	Intensity (cd)	Luminous Flux (lm)	Driver Options
10W	12W	WARM : 2700K	15°	8997	840	ND, AN, DA
		WARM : 3000K	24°	4855		
		NATURAL : 4000K	38°	1997		

Data are based on 3000K. Nominal data of 2700K and 3500K are shared with 3000K.
Higher CCT of 4000K and 5000K will have a nominal data value of 5% higher than published.

the table information is at nominal values accuracy of +/-7%
nominal CRI >95, equal to Ra >90-97, R9 > 50

DETAILS SPECIFICATION

Family Type	Space ² Series
Mains Voltage	DC 48V
Lifetime	50,000 hours (80% lumen maintenance at Ta = 25°C)
Dimming	0-10V, DALI
Mains Connection	Magnetic track
Materials	Aluminium, plastic
Fire Safety	VW-1
Flammability Mark	F
IP Code	IP20
Safety Class	Class 3
Standards	IEC 60598-1, IEC 61347-2-13
Regulatory Markings	CE, CCC, RoHS

ORDERING MATRIX CHART

FIXTURE			LED MODULE				DRIVER
Type	Colour	Accessories	LED Power	Beam Angle	Colour Temp	CRI	Dimming
S-PENDANT	—	—	—	—	—	—	—
	MB Matt Black	None	10 10W	15 15°	27 2700K	PA ProART	ND Non-Dim
		AGL Anti-Glare Louvre		24 24°	30 3000K		AN 0-10V
		SL Soft Lens		38 38°	40 4000K		DA DALI

example: S-PENDANT.MB.10.15.30.PA.ND