

# SPACE<sup>2</sup> WALLWASH

12W MAGNETIC TRACK  
LUMINAIRE

- Supplied with non-dimmable or 0-10V/DALI dimmable LED driver
- >65lm/W module
- Colour rendering index: 95
- Colour temperature options: 2700K, 3000K, 4000K
- Beam pattern options: 38° x 130° at 45° optical tilt
- 3 steps MacAdam ellipse binning
- Uniform and comfort light
- DC 48V
- IP20



FIXTURE COLOUR



Matt Black

## AVAILABLE OPTIONS

DRIVER



(ND)



(AN)



(DA)

COLOUR TEMPERATURE



2700K

3000K

4000K




ProART

BEAM ANGLE



38° (H) X 130° (V)

## DIMENSIONS (MM)



### SYSTEM SPECIFICATIONS

LED Lamp Power	LED System Power	Colour Temperature	Beam Angle	PROART CRI 95		Driver Options
				Intensity (cd)	Luminous Flux (lm)	
12W	15W	WARM : 2700K WARM : 3000K NATURAL : 4000K	38°(H) x 130°(W)	897	796	ND, AN, DA

Data are based on 3000K. Nominal data of 2700K and 3500K are shared with 3000K. Higher CCT of 4000K and 5000K will have a nominal data value of 5% higher than published.

the table information is at nominal values accuracy of +/-7% nominal CRI >95, equal to Ra >90-97, R9 > 50

### DETAILS SPECIFICATION

Family Type	Space <sup>2</sup> Series
Mains Voltage	DC 48V
Lifetime	50,000 hours (80% lumen maintenance at Ta = 25°C)
Dimming	0-10V, DALI
Mains Connection	Magnetic track
Materials	Aluminium, plastic
Fire Safety	VW-1
Flammability Mark	F
IP Code	IP20
Safety Class	Class 3
Standards	IEC 60598-1, IEC 61347-2-13
Regulatory Markings	CE, CCC, RoHS

### ORDERING MATRIX CHART

FIXTURE		LED MODULE				DRIVER
Type	Colour	LED Power	Beam Angle	Colour Temp	CRI	Dimming
<b>S-WALLWASH</b>	---	---	---	---	---	---
	<b>MB</b> Matt Black	<b>12</b> 12W	<b>38X130</b> 38°x130°	<b>27</b> 2700K	<b>PA</b> ProART	<b>ND</b> Non-Dim
				<b>30</b> 3000K		<b>AN</b> 0-10V
				<b>40</b> 4000K		<b>DA</b> DALI

example: S-WALLWASH.MB.12.38X130.30.PA.ND