

BUTTON MICRO FIX

1W / 2W CABINET DEEP
RECESSED MOUNTED
LUMINAIRE



- High CRI, Excellent glare control
- Supplied with non-dimmable or phase/0-10V/DALI dimmable LED driver
- >74 lm/W module
- Colour rendering index: 95
- Colour temperature options: 2700K, 3000K
- Beam pattern options: 15°, 20°, 25°, 35°
- 3 steps MacAdam ellipse binning
- Uniform and comfort light
- Aluminium & Plastic Material
- Ø33mm cutout
- IP20

FIXTURE COLOUR OPTIONS

-  Matt White
-  Matt Black
-  Chrome "Dark Light Reflector"
-  Black "Dark Light Reflector"

AVAILABLE OPTIONS


TEMPERATURE



DRIVER




BEAM ANGLE



DIMENSIONS (MM)

**Displayed height measurements are for highest point of tilting.*



SYSTEM SPECIFICATIONS

				PROART CRI 95		
LED Lamp Power	LED System Power	Colour	Beam Angle	Intensity (cd)	Luminous Flux	Driver Options
1W	1.7W	WARM : 2700K WARM : 3000K	15°	650	79	ND, PH, AN, DA
			20°	450		
			25°	400		
			35°	250		
2W	3.2W		15°	1070	148	
			20°	740		
			25°	690		
			35°	440		

Data are based on 3000K. Nominal data of 2700K and 4000K are shared with 3000K. Higher CCT of 4000K will have a nominal data value of 5% higher than published.

the table information is at nominal values accuracy of +/-7% nominal CRI ~95, equal to Ra >90-97, R9 > 50

DETAILS SPECIFICATION

Family Type	Button Series
Mains voltage	220-240V
Colour options	Matt Black, Matt White, Chrome, Chrome Black
Installation Compatibility	Button Micro
Lifetime	50,000 HOURS (80% lumen maintenance at Ta = 25°C)
Dimming	Phase (triac) dimmer, 0-10V, DALI
Mains connection	Screw terminal connection
Materials	Aluminium, plastic
Fire safety	VW-1
Flammability mark	F
IP code	IP20
Safety class	Class 2
Standards	IEC 60598-1, IEC 61347-2-13
Regulatory markings	CE, CCC
Dimensions	Ø39 x 39mm

FIXTURE			LED MODULE				DRIVER
Type	Angle	Colour	LED Power	Beam Angle	Colour Temp	CRI	Dimming
BUTTON-MICRO	---	---	---	---	---	---	---
FX Fix	WH Matt White	1 1W	15 15°	27 2700K	PA ProART	ND Non-Dim	
	MB Matt Black	2 2W	20 20°	30 3000K		PH Phase	
	CR Chrome		25 25°			AN 0-10V	
	CB Chrome Black		35 35°			DA DALI	

example: *BUTTON-MICRO.FX.WH.1.15.27.PA.ND*