





# BUTTON FIX

1W / 2W CABINET  
RECESSED MOUNTED  
LUMINAIRE



- FIXTURE COLOUR OPTIONS
-  Matt White
  -  Matt Black
  -  Chrome
  -  Chrome Black

- High CRI, excellent glare control
- Supplied with non-dimmable or phase/1-10V/DALI dimmable LED driver
- >74 lm/W module
- Colour rendering index: 95
- Colour temperature options: 2700K, 3000K
- Beam pattern options: 15°, 20°, 25°, 30°
- 3 steps MacAdam ellipse binning
- Uniform and comfort light
- IP20
- Ø33mm cutout

## AVAILABLE OPTIONS


### DRIVER




### COLOUR TEMPERATURE



### BEAM ANGLE



## DIMENSIONS (MM)



### SYSTEM SPECIFICATIONS

				PROART CRI 95		
LED Lamp Power	LED System Power	Colour Temperature	Beam Angle	Intensity (cd)	Luminous Flux (lm)	Driver Options
1W	1.7W	WARM : 2700K WARM : 3000K	15°	650	79	ND, PH, AN, DA
			20°	450		
			25°	400		
			30°	250		
2W	3.2W		15°	1070	148	
			20°	740		
			25°	690		
			30°	440		

Data are based on 3000K. Nominal data of 2700K and 4000K are shared with 3000K. Higher CCT of 4000K will have a nominal data value of 5% higher than published.

the table information is at nominal values accuracy of +/-7% nominal CRI ~95, equal to Ra >90-97, R9 > 50

### DETAILS SPECIFICATION

Family Type	Button Series
Mains Voltage	220-240V
Lifetime	50,000 hours (80% lumen maintenance at Ta = 25°C)
Dimming	Phase (trailing edge), 1-10V, DALI
Mains Connection	Screw terminal connection
Materials	Aluminium, plastic
Fire Safety	VW-1
Flammability Mark	F
IP Code	IP20
Safety Class	Class 2
Standards	IEC 60598-1, IEC 61347-2-13
Regulatory Markings	CE, CCC, RoHS

### ORDERING MATRIX CHART

FIXTURE			LED MODULE				DRIVER
Type	Angle	Colour	LED Power	Beam Angle	Colour Temp	CRI	Dimming
<b>BUTTON</b>							
<b>FX</b> Fix	<b>WH</b> Matt White	<b>1</b> 1W	<b>15</b> 15°	<b>27</b> 2700K	<b>PA</b> ProART	<b>ND</b> Non-Dim	
	<b>MB</b> Matt Black	<b>2</b> 2W	<b>20</b> 20°	<b>30</b> 3000K		<b>PH</b> Phase	
	<b>CR</b> Chrome		<b>25</b> 25°			<b>AN</b> 1-10V	
	<b>CB</b> Chrome Black		<b>30</b> 30°			<b>DA</b> DALI	

example: **BUTTON.FX.WH.1.15.27.PA.ND**