


# BUTTON MINI FIX

3W CABINET RECESSED  
MOUNTED LUMINAIRE



- Supplied with non-dimmable or phase/1-10V/DALI dimmable LED driver
- >76 lm/W module
- Colour rendering index: 95
- Colour temperature options: 2700K, 3000K, 4000K, 5000K
- Beam pattern options: 24°, 38°
- 3 steps MacAdam ellipse binning
- Uniform and comfort light
- Ø61mm cutout
- IP20

FIXTURE  
COLOUR OPTIONS



AVAILABLE OPTIONS


TEMPERATURE



DRIVER




BEAM ANGLE



DIMENSIONS (MM)

\*Displayed height measurements are for highest point of tilting.



### SYSTEM SPECIFICATIONS

| LED Lamp Power | LED System Power | Colour  | Beam Angle | PROART CRI 95  |               | Driver Options |
|----------------|------------------|---|------------|----------------|---------------|----------------|
|                |                  |   |            | Intensity (cd) | Luminous Flux |                |
| 3W             | 4.5W             | WARM : 2700K                                    | 24°        | 553            | 230           | ND, PH, AN, DA |
|                |                  | WARM : 3000K<br>NATURAL : 4000K<br>COOL : 5000K | 38°        | 357            |               |                |

Data are based on 3000K. Nominal data of 2700K and 4000K are shared with 3000K. Higher CCT of 4000K will have a nominal data value of 5% higher than published.

the table information is at nominal values accuracy of +/-7% nominal CRI -95, equal to Ra >90-97, R9 > 50

### DETAILS SPECIFICATION

|                            |   |
|----------------------------|---|
| Family Type                | Button Series                                     |
| Mains voltage              | 220-240V  |
| Colour options             | Matt Black, Matt White                            |
| Installation Compatibility | Button Mini                                       |
| Lifetime                   | 50,000 HOURS (80% lumen maintenance at Ta = 25°C) |
| Dimming                    | Phase (triac) dimmer, 1-10V, DALI                 |
| Mains connection           | Screw terminal connection                         |
| Materials                  | Aluminium, plastic                                |
| Fire safety                | Glow wire test 750°C, UL94V-0, VW-1               |
| Flammability mark          | F   |
| IP code                    | IP20  |
| Safety class               | Class 2   |
| Standards                  | IEC 60598-1, IEC 61347-2-13                       |
| Regulatory markings        | CE, RoHs  |
| Weight                     | 0.2kg   |
| Dimensions                 | Ø70 x 41mm  |

| FIXTURE            |                      |             | LED MODULE    |                 |                  |                   | DRIVER  |
|--------------------|----------------------|-------------|---------------|-----------------|------------------|-------------------|---------|
| Type               | Angle                | Colour      | LED Power     | Beam Angle      | Colour Temp      | CRI               | Dimming |
| <b>BUTTON-MINI</b> | —                    | —           | —             | —               | —                | —                 | —       |
| <b>FX</b> Fix      | <b>WH</b> Matt White | <b>3</b> 3W | <b>24</b> 24° | <b>27</b> 2700K | <b>PA</b> ProART | <b>ND</b> Non-Dim |         |
|                    | <b>MB</b> Matt Black |             | <b>38</b> 38° | <b>30</b> 3000K |                  | <b>PH</b> Phase   |         |
|                    |                      |             |               | <b>40</b> 4000K |                  | <b>AN</b> 1-10V   |         |
|                    |                      |             |               | <b>50</b> 5000K |                  | <b>DA</b> DALI    |         |

example: *BUTTON-MINI.FX.WH.3.24.27.PA.ND*