

# BUTTON TILT

1W / 2W CABINET  
RECESSED MOUNTED  
LUMINAIRE



- High CRI, Excellent glare control
- Supplied with non-dimmable or phase/0-10V/DALI dimmable LED driver
- >82 lm/W module
- Colour rendering index: 95
- Colour temperature options: 2700K, 3000K
- Beam pattern options: 15°, 20°, 25°, 35°
- 3 steps MacAdam ellipse binning
- Uniform and comfort light
- Aluminium & Plastic Material
- Ø35mm cutout
- IP20

## FIXTURE COLOUR OPTIONS

-  Matt White
-  Matt Black
-  Chrome "Dark Light Reflector"
-  Black "Dark Light Reflector"

## AVAILABLE OPTIONS


### TEMPERATURE



### DRIVER




### BEAM ANGLE



## DIMENSIONS (MM)

*\*Displayed height measurements are for highest point of tilting.*



### SYSTEM SPECIFICATIONS

				PROART CRI 95		
LED Lamp Power	LED System Power	Colour	Beam Angle	Intensity (cd)	Luminous Flux	Driver Options
1W	1.7W	WARM : 2700K WARM : 3000K	15°	660	94	ND, PH, AN, DA
			20°	430		
			25°	390		
			35°	240		
2W	3.2W		15°	1140	165	
			20°	840		
			25°	720		
			35°	400		

Data are based on 3000K. Nominal data of 2700K and 4000K are shared with 3000K. Higher CCT of 4000K will have a nominal data value of 5% higher than published.

the table information is at nominal values accuracy of +/-7% nominal CRI >95, equal to Ra >90-97, R9 > 50

### DETAILS SPECIFICATION

Family Type	Button Series
Mains voltage	220-240V
Colour options	Matt Black, Matt White, Chrome, Chrome Black
Installation Compatibility	Button Tilt
Lifetime	50,000 HOURS (80% lumen maintenance at Ta = 25°C)
Dimming	Phase (triac) dimmer, 0-10V, DALI
Mains connection	Screw terminal connection
Materials	Aluminium, plastic
Fire safety	VW-1
Flammability mark	F
IP code	IP20
Safety class	Class 2
Standards	IEC 60598-1, IEC 61347-2-13
Regulatory markings	CE, CCC
Dimensions	Ø39 x 40mm

FIXTURE			LED MODULE				DRIVER
Type	Angle	Colour	LED Power	Beam Angle	Colour Temp	CRI	Dimming
<b>BUTTON</b>	---	---	---	---	---	---	---
<b>TL</b>	Tilt	<b>WH</b> Matt White	<b>1</b> 1W	<b>15</b> 15°	<b>27</b> 2700K	<b>PA</b> ProART	<b>ND</b> Non-Dim
		<b>MB</b> Matt Black	<b>2</b> 2W	<b>20</b> 20°	<b>30</b> 3000K		<b>PH</b> Phase
		<b>CR</b> Chrome		<b>25</b> 25°			<b>AN</b> 0-10V
		<b>CB</b> Chrome Black		<b>35</b> 35°			<b>DA</b> DALI

example: **BUTTON.TL.WH.1.15.27.PA.ND**