

BUTTON ZOOM

3W CABINET RECESSED
MOUNTED LUMINAIRE



FIXTURE
COLOUR OPTIONS



Matt White



Matt Black

- Supplied with non-dimmable or phase/1-10V/DALI dimmable LED driver
- >60 lm/W module
- Colour rendering index: 95
- Colour temperature options: 2700K, 3000K, 4000K, 5000K
- Beam pattern options: zoomable 15°-40°
- 3 steps MacAdam ellipse binning
- Uniform and comfort light
- Ø56mm cutout
- IP20

AVAILABLE OPTIONS

TEMPERATURE



ProART

DRIVER



(ND)



(PH)




(AN)



(DA)


BEAM ANGLE



zoomable 15° - 40°

DIMENSIONS (MM)

**Displayed height measurements are for highest point of tilting.*



SYSTEM SPECIFICATIONS

LED Lamp Power	LED System Power	Colour	Beam Angle	PROART CRI 95		Driver Options
				Intensity (cd)	Luminous Flux	
3W	4.5W	WARM : 2700K WARM : 3000K NATURAL : 4000K COOL : 5000K	zoomable 15°-40°	900 - 425	148 - 189	ND, PH, AN, DA

Data are based on 3000K. Nominal data of 2700K and 4000K are shared with 3000K. Higher CCT of 4000K will have a nominal data value of 5% higher than published.

the table information is at nominal values accuracy of +/-7% nominal CRI -95, equal to Ra >90-97, R9 > 50

DETAILS SPECIFICATION

Family Type	Button Series
Mains voltage	220-240V
Colour options	Matt Black, Matt White
Installation Compatibility	Button Zoom
Lifetime	50,000 HOURS (80% lumen maintenance at Ta = 25°C)
Dimming	Phase (triac) dimmer, 1-10V, DALI
Mains connection	Screw terminal connection
Materials	Aluminium, plastic
Fire safety	Glow wire test 750°C, UL94V-0, VW-1
Flammability mark	F
IP code	IP20
Safety class	Class 2
Standards	IEC 60598-1, IEC 61347-2-13
Regulatory markings	CE, RoHs
Weight	0.2kg
Dimensions	Ø70 x 41mm

FIXTURE		LED MODULE				DRIVER
Type	Colour	LED Power	Beam Angle	Colour Temp	CRI	Dimming
BUTTON-ZOOM						
	WH Matt White	3 3W	15Z40 15°-40°	27 2700K	PA ProART	ND Non-Dim
	MB Matt Black			30 3000K		PH Phase
				40 4000K		AN 1-10V
				50 5000K		DA DALI

example: *BUTTON-ZOOM.WH.3.15Z40.27.PA.ND*