


STARLITE MICRO

0.6 WATT FLOOR LIGHT



- Compact, Recessed, stylish construction
- >15 lm/W module
- Colour rendering index: 85
- Colour temperature options: 2700K, 3000K, 4000K
- Beam pattern options: 70°
- Uniform and comfort light
- Ø22mm cutout
- IP68 IK10

FIXTURE
COLOUR OPTIONS



Chrome



Matt Black

AVAILABLE OPTIONS

DRIVER



(24V)

TEMPERATURE



BEAM ANGLE

70°



DIMENSIONS (MM)

**Displayed height measurements are for highest point of tilting.*



Cut Ø 22

SYSTEM SPECIFICATIONS

LED Lamp Power	Colour	Beam Angle	STANDARD CRI 85	
			Intensity (cd)	Luminous Flux
0.6W	WARM : 2700K WARM : 3000K NATURAL : 4000K	70°	3	9

Data are based on 3000K. Nominal data of 2700K and 3500K are shared with 3000K.
Higher CCT of 4000K and 5000K will have a nominal data value of 5% higher than published.

the table information is at nominal values accuracy of +/-7% nominal CRI >85, equal to Ra >80-87, R9 > 0 nominal CRI >95, equal to Ra >90-97, R9 > 50

DETAILS SPECIFICATION

Family Type	Starlite Miniature Series
Mains voltage	24V DC
Colour options	Chrome, Matt Black
Installation Compatibility	Starlite Micro
Lifetime	50,000 HOURS (80% lumen maintenance at Ta = 25°C)
Mains connection	Screw terminal connection
Materials	SS304/SS316L
Flammability mark	F
IP code	IP68
Safety class	Class 3
Weight	0.06kgs
Dimensions	Ø26 x 24.5mm
IK Rating	IK10
Warranty	3 Years

FIXTURE		LED MODULE			
Type	Colour	LED Power	Beam Angle	Colour Temp	CRI
STARLITE-MICRO	CR Chrome	0 0.6W	70 70°	27 2700K	Standard
	MB Matt Black			30 3000K	
				40 4000K	

example: STARLITE-MICRO.CR.0.70.27