






BLOCK SURFACE

6.3W SURFACE MOUNTED LUMINAIRE



- Supplied with non-dimmable or phase/0-10V/DALI dimmable LED driver
- >80 lm/W module
- Colour rendering index: 95
- Colour temperature options: 2700K, 3000K, 4000K, 5000K
- Beam pattern options: 12°, 34°, 48°
- 3 steps MacAdam ellipse binning
- Uniform and comfort light
- IP20
- Dimension: 82 x 60 x 32mm

FIXTURE COLOUR OPTIONS

-  Matt White
-  Matt Black
-  Chrome
-  Copper

AVAILABLE OPTIONS


TEMPERATURE



DRIVER




BEAM ANGLE



DIMENSIONS (MM)

**Displayed height measurements are for highest point of tilting.*



SYSTEM SPECIFICATIONS

LED Lamp Power	LED System Power	Colour	Beam Angle	PROART CRI 95		Driver Options
				Intensity (cd)	Luminous Flux	
6.3W	7.2W	WARM : 2700K	12°	4730	510	ND, PH, AN, DA
		WARM : 3000K	34°	1130		
		NATURAL : 4000K	48°	865		
		COOL : 5000K				

Data are based on 3000K. Nominal data of 2700K and 3500K are shared with 3000K.
Higher CCT of 4000K and 5000K will have a nominal data value of 5% higher than published.

the table information is at nominal values accuracy of +/-7%
nominal CRI -85, equal to Ra >80-87, R9 > 0
nominal CRI -95, equal to Ra >90-97, R9 > 50

DETAILS SPECIFICATION

Family Type	Block Series
Mains voltage	220-240V
Colour options	Matt Black, Matt White, Chrome, Copper
Installation Compatibility	Block Surface
Lifetime	50,000 HOURS (80% lumen maintenance at Ta = 25°C)
Dimming	Phase, 1-10V, DALI
Mains connection	Screw terminal connection
Materials	Aluminium, plastic
Fire safety	Glow wire test 750°C, UL94V-0, VW-1
Flammability mark	F
IP code	IP20
Safety class	Class 2
Standards	IEC 60598-1, IEC 61347-2-13
Regulatory markings	CE, CB, RCM
Dimensions	82 x 60 x 32mm

FIXTURE		LED MODULE				DRIVER
Type	Colour	LED Power	Beam Angle	Colour Temp	CRI	Dimming
BLOCK-SM						
WH	Matt White	6 6.3W	12 12°	27 2700K	PA ProART	ND Non-Dim
MB	Matt Black		34 34°	30 3000K		PH Phase
CR	Chrome		48 48°	40 4000K		AN 0-10V
CP	Copper			50 5000K		DA DALI

example: BLOCK-SM.WH.6.12.30.PA.ND