






# CUBE WALL MOUNT

8.4W INDOOR WALL  
MOUNTED LUMINAIRE




FIXTURE  
COLOUR OPTIONS

-  Matt White
-  Matt Black
-  Chrome
-  Copper

- Supplied with non-dimmable LED driver
- >80 lm/W module
- Colour rendering index: 95
- Colour temperature options: 2700K, 3000K, 4000K, 5000K
- Beam pattern options: 12°
- 3 steps MacAdam ellipse binning
- Uniform and comfort light
- IP20

## AVAILABLE OPTIONS

### BEAM ANGLE



### COLOUR TEMPERATURE




### DRIVER



(ND)

## DIMENSIONS (MM)



### SYSTEM SPECIFICATIONS

				PROART CRI 95		
LED Lamp Power	LED System Power	Colour Temperature	Beam Angle	Intensity (cd)	Luminous Flux (lm)	Driver Options
8.4W	9.5W	WARM : 2700K WARM : 3000K NATURAL : 4000K COOL : 5000K	12°	6350	680	ND

Data are based on 3000K. Nominal data of 2700K and 3500K are shared with 3000K. Higher CCT of 4000K and 5000K will have a nominal data value of 5% higher than published. the table information is at nominal values accuracy of +/-7% nominal CRI -95, equal to Ra >90-97, R9 > 50

### DETAILS SPECIFICATION

Family Type	Cube Series
Mains Voltage	220-240V
Lifetime	50,000 hours (80% lumen maintenance at Ta = 25°C)
Dimming	Non-dimmable
Mains Connection	Screw terminal connection
Materials	Aluminium, plastic
Fire Safety	Glow wire test 850°C, UL94V-0, VW-1
Flammability Mark	F
IP Code	IP20
Safety Class	Class 2
Standards	IEC 60598-1, IEC 61347-2-13
Regulatory Markings	CE, ENEC, RoHS
Weight	0.25kg

### ORDERING MATRIX CHART

FIXTURE		LED MODULE				DRIVER
Type	Colour	LED Power	Beam Angle	Colour Temp	CRI	Dimming
<b>CUBE-WM</b>						
<b>WH</b>	Matt White	<b>8</b> 8.4W	<b>12</b> 12°	<b>27</b> 2700K	<b>PA</b> ProART	<b>ND</b> Non-Dim
<b>MB</b>	Matt Black			<b>30</b> 3000K		
<b>CR</b>	Chrome			<b>40</b> 4000K		
<b>CP</b>	Copper			<b>50</b> 5000K		

example: CUBE-WM.WH.8.12.30.PA.ND