



MODI 3 TRACK

TRACK LUMINAIRE



AVAILABLE OPTIONS	
FIXTURE COLOUR OPTIONS	 Matt White RAL 9003  Matt Black RAL 9011
SNOOT	 Full Snoot  45 Dgree Snoot  Barn Door
ACCESSORIES	 Honeycomb Anti-Glare Louvre  Soft Lens  Linear Spread Lens  Wallwash Lens
LED MODULE	 2700K  3000K  3500K  4000K  ProART  ProART98  tuneWHITE  10°  15°  20°  30°  40°
DRIVER DIMMING	 ND  PH  AN  DA  DT8  DMX  CSB

MODI 3
TRACK

DIMENSIONS (MM)


MODI 3 TRACK

ORDERING MATRIX CHART

Fixture				LED Module								Driver - Integrated Track Adapter			
Type	Colour		Snoot		LED Power		Beam Angle		Colour Temp		CRI		Dimming		
MODI-3TR															
	WH	Matt White	FS	Full Snoot	18	18W	10	10°	27	2700K	PA	ProART95	ND.I3AC	Non-Dim Integrated 3 Circuit AC	
	MB	Matt Black	45S	45 Degree Snoot			15	15°	30	3000K	PP	ProART98	PH.I3AC	Phase-Dim Integrated 3 Circuit AC	
			BD	Barn Door			20	20°	35	3500K			AN.I1DT	0-10V Integrated 1 Circuit AC + Data	
						30	30°	40	4000K	DA.I1DT			DALI Integrated 1 Circuit AC + Data		
						40	40°			DA.I3DT			DALI Integrated 3 Circuit AC + Data		
													LBA.I3AC	Local Brightness Adjuster Integrated 3 Circuit AC	
													DMX.I1DT	DMX Integrated 1 Circuit AC + Data	
													CSB.I3AC	Casambi Integrated 3 Circuit AC	
								TW2755	tuneWHITE 2700K-5500K	PA	ProART95	DT8.I1DT	DALI DT8 Integrated 1 Circuit AC + Data		
												DT8.I3DT	DALI DT8 Integrated 3 Circuit AC + Data		
												DMX.I1DT	DMX Integrated 1 Circuit AC + Data		
												CSB.I3AC	Casambi Integrated 3 Circuit AC		

example: MODI-3TR.MB.FS.18.30.30.PA.DA.I3DT

Accessories		
Type	Accessory	Fixture
SC.ACC		-MODI-3
	AGL	Anti-Glare Louvre
	SL	Soft Lens
	LSL	Linear Spread Lens
	WWL	Wall Wash Lens

example: SCP.ACC.AGL-MODI-3

*WWL is recommended to be used with 20° beam angle for optimum effect.