

VEGA

PENDANT SERIES

A series of ceiling hung pendant luminaires with versatility of having different accessories. Vega series luminaires are available in 3 power variants that are ideal for illuminating designated areas and objects in all kinds of spaces.



Multiple accessories options



Snout
(included)



Honeycomb
Anti-Glare Louvre



Cross
Louvre



Barn Door




Wallwash
Ring

Module Colour Temperature Variation



ProART

Beam Angle



Driver Dimming Variation



(ND)



(PH)



(AN)



(DA)

VEGA PENDANT

26W / 17W / 12W PENDANT MOUNTED LUMINAIRE

26W, 17W



12W



AVAILABLE OPTIONS

FIXTURE COLOUR OPTIONS

MATT WHITE RAL9003

MATT BLACK RAL9011



ACCESSORIES

26W, 17W
12W



Shoot
(included)



Honeycomb
Anti-Glare Louvre



Cross
Louvre



Barn Door

26W, 17W



Wallwash
Ring

LED MODULE

SINGLE CCT



2700K



3000K



4000K




5000K




ProART

26W, 17W



12W



DRIVER DIMMING



(ND)



(PH)




(AN)



(DA)

*External drivers for 1-10V
(26W) and DALI (26W, 17W,
12W) options.

DIMENSIONS (MM)



SPECIFICATIONS

Family Type	Vega Series
Mains Voltage	220-240V, 50Hz
Typical Operating Voltage	36V
Typical Operating Current	700mA (26W), 500mA (17W), 350mA (12W)
Lifetime	50,000 hours (80% lumen maintenance at Ta = 25°C), B10
Beam Angles	26W, 17W - 15°, 24°, 38°, 60°
	12W - 12°, 24°, 36°, 60°
Colour Temperatures	2700K, 3000K, 4000K, 5000K
CRI	ProART (CRI=95)
SDCM	3 steps MacAdam ellipse binning

Driver (Dimming)	Non-dim, phase (leading & trailing edge), 0-10V, DALI
Mains Connection	Push-pin or screw terminals for convenient connection
Materials	Aluminium, plastic
Fire Safety	Glow wire test 850°C, UL94V-0, VW-1
Flammability Mark	F
Ingress Protection	IP40
Safety Class	Class 2
Standards	IEC 60598-1, IEC 61347-2-13
Regulatory Markings	CE, CCC, RCM, ETL, RoHS
Weight	1.0kg (26W, 17W), 0.6kg (12W)

PHOTOMETRICS

VEGA 26W

Height (m)		Emax (lx)			
		12°	24°	36°	60°
1	E(0°)	14109	9775	6414	3003
	Cone Ø (m)	0.33	0.46	0.63	1.08
2	E(0°)	3527	2444	1603	751
	Cone Ø (m)	0.66	0.92	1.26	2.15
3	E(0°)	1568	1086	713	334
	Cone Ø (m)	0.99	1.37	1.89	3.23
4	E(0°)	882	611	401	188
	Cone Ø (m)	1.32	1.83	2.52	4.31
5	E(0°)	564	391	257	120
	Cone Ø (m)	1.66	2.29	3.15	5.38

Correction Factor: VEGA 17W - f = 0.67

VEGA 26W, 17W			Luminous Flux (lm)
LED Power	System Power	CRI	3000K
			12°, 24°, 36°, 60°
26W	30W	ProART CRI=95	2700
17W	20W	ProART CRI=95	1800

Data are based on 3000K (ProART CRI=95). Nominal data of 2700K and 3500K are shared with 3000K.
Higher CCT of 4000K and 5000K will have a nominal data value of 5% higher than published. (f = 1.05)
Nominal CRI=95, equals to Ra>90-97, R9>50

VEGA 12W

Height (m)		Emax (lx)			
		12°	24°	36°	60°
1	E(0°)	7113	4498	2836	1168
	Cone Ø (m)	0.28	0.43	0.60	1.15
2	E(0°)	1778	1124	709	292
	Cone Ø (m)	0.57	0.86	1.19	2.30
3	E(0°)	790	500	315	130
	Cone Ø (m)	0.85	1.30	1.79	3.45
4	E(0°)	445	281	177	73
	Cone Ø (m)	1.14	1.73	2.38	4.60
5	E(0°)	285	180	113	47
	Cone Ø (m)	1.42	2.16	2.98	5.75

Data are based on 3000K (ProART CRI=95). Nominal data of 2700K and 3500K are shared with 3000K.
Higher CCT of 4000K and 5000K will have a nominal data value of 5% higher than published. (f = 1.05)
Nominal CRI=95, equals to Ra>90-97, R9>50

ORDERING MATRIX CHART

Fixture				LED Module					Driver	
Type	Colour		Accessories	LED Power		Beam Angle		Colour Temp	CRI	
VEGA-PM	WH	Matt White	S	26	26W	15	15°	2700K	PA	ProART
			AGL							
			CL							
			BD							
			WR							
	MB	Matt Black		17	17W	24	24°	3000K		
				12	12W	12	12°	4000K		
						24	24°	5000K		
						36	36°			
						60	60°			

*Snoot accessory is included by default

**Wallwash Ring accessory is only valid with 26W, 17W models

example: VEGA-PM.WH.S.12.12.30.PA.ND