

VEGA SURFACE

12W / 17W / 26W
SURFACE MOUNTED
LUMINAIRE



FIXTURE
COLOUR OPTIONS



Matt White



Matt Black

ELR[®]



- Supplied with non-dimmable or phase/1-10V/DALI dimmable LED driver
- >110 lm/W module
- Colour rendering index: 95
- Colour temperature options: 2700K, 3000K, 4000K, 5000K
- Beam pattern options: 12°, 24°, 36°, 60° (12W)
15°, 18°, 24°, 38°, 60° (17W, 26W)
- 3 steps MacAdam ellipse binning
- Uniform and comfort light
- IP20

AVAILABLE OPTIONS

TEMPERATURE



ProART

DRIVER



(ND)



(PH)




(AN)



(DA)


BEAM ANGLE

12W



12°, 24°, 36°, 60°

17W, 26W



15°, 18°, 24°, 38°, 60°

ACCESSORIES



Honeycomb
Anti-Glare Louvre



Cross
Louvre



Barn Door



Wallwash Ring



Eye Snoot




Snoot


DIMENSIONS (MM)

*Displayed height measurements are for
highest point of tilting.

(12W)



(17W, 26W)



SYSTEM SPECIFICATIONS

				PROART CRI 95		
LED Lamp Power	LED System Power	Colour	Beam Angle	Intensity (cd)	Luminous Flux	Driver Options
12W	15W	WARM : 2700K WARM : 3000K NATURAL : 4000K COOL : 5000K	12°	8330	1090	ND, PH, AN, DA
			24°	4675		
			36°	3417		
			60°	1275		
17W	20W		15°	11059	2060	
			18°	8279		
			24°	6962		
			38°	5100		
26W	30W		60°	2278	2690	
			15°	14544		
			18°	11875		
			24°	9359		
		38°	6307			
		60°	3188			

Data are based on 3000K. Nominal data of 2700K and 4000K are shared with 3000K.
Higher CCT of 4000K will have a nominal data value of 5% higher than published.

the table information is at nominal values accuracy of +/-7%
nominal CRI -95, equal to Ra >90-97, R9 > 50

DETAILS SPECIFICATION

Family Type	Vega Series	Fire safety	Glow wire test 750°C, UL94V-0, VW-1
Mains voltage	220-240V	Flammability mark	F
Colour options	Matt White, Matt Black	IP code	IP20
Installation Compatibility	Vega Surface	Safety class	Class 2
Lifetime	50,000 HOURS (80% lumen maintenance at Ta = 25°C)	Standards	IEC 60598-1, IEC 61347-2-13
Dimming	Phase (triac) dimmer, 1-10V, DALI	Regulatory markings	CE, RoHS, ETL, SAA, CCC
Mains connection	Screw terminal connection	Weight	0.5kg (12W) / 1.0kg (17W, 26W)
Materials	Aluminium, plastic	Dimensions	Ø60 x 157mm / Ø84 x 181mm
Accessories	Honeycomb Anti-Glare Louvre, Cross Louvre, Barn Door (12W) Honeycomb Anti-Glare Louvre, Cross Louvre, Barn Door, Wallwash Ring, Eye Snoot, Snoot (17W, 26W)		

FIXTURE			LED MODULE				DRIVER
Type	Colour	Accessories	LED Power	Beam Angle	Colour Temp	CRI	Dimming
VEGA-SM	---	---	---	---	---	---	---
WH	Matt White	None	12 12W	12 12°	27 2700K	PA ProART	ND Non-Dim
MB	Matt Black	AGL Anti-Glare Louvre		24 24°	30 3000K		PH Phase
		CL Cross Louvre		36 36°	40 4000K		AN 1-10V
		BD Barn Door		60 60°	50 5000K		DA DALI
		WR Wallwash Ring	17 17W	15 15°			
		ES Eye Snoot	26 26W	18 18°			
		S Snoot		24 24°			
				38 38°			
				60 60°			

example: VEGA-SM.WH.12.12.30.PA.ND