

VEGA ZOOM PENDANT

12W / 17W / 26W
PENDANT MOUNTED
LUMINAIRE



FIXTURE
COLOUR OPTIONS



Matt White



Matt Black

ELR[®]



- Supplied with non-dimmable or phase/1-10V/DALI dimmable LED driver
- >80 lm/W module
- Colour rendering index: 95
- Colour temperature options: 2700K, 3000K, 4000K, 5000K
- Beam pattern options: zoomable 15° - 45° (12W)
zoomable 25° - 60° (17W, 26W)
- 3 steps MacAdam ellipse binning
- Uniform and comfort light
- IP20

AVAILABLE OPTIONS

TEMPERATURE



ProART

DRIVER



(ND)



(PH)



(AN)



(DA)

1-10V and DALI driver are external mounted driver.


BEAM ANGLE

12W



zoomable 15° - 45°

17W, 26W



zoomable 25° - 60°

ACCESSORIES




Honeycomb
Anti-Glare Louvre


DIMENSIONS (MM)

*Displayed height measurements are for highest point of tilting.

(12W)



(17W, 26W)



SYSTEM SPECIFICATIONS

				PROART CRI 95		
LED Lamp Power	LED System Power	Colour	Beam Angle	Intensity (cd)	Luminous Flux	Driver Options
12W	15W	WARM : 2700K	zoomable 15°-45°	8016 - 2287	836 - 1066	ND, PH, AN, DA
17W	20W	WARM : 3000K NATURAL : 4000K	zoomable 25°-60°	7769 - 1649	1559 - 1758	
26W	30W	COOL : 5000K		10600 - 2372	1797 - 2058	

Data are based on 3000K. Nominal data of 2700K and 4000K are shared with 3000K. Higher CCT of 4000K will have a nominal data value of 5% higher than published.

the table information is at nominal values accuracy of +/-7% nominal CRI -95, equal to Ra >90-97, R9 > 50

DETAILS SPECIFICATION

Family Type	Vega Zoom Series
Mains voltage	220-240V
Colour options	Matt Black, Matt White
Installation Compatibility	Vega Zoom Pendant
Lifetime	50,000 HOURS (80% lumen maintenance at Ta = 25°C)
Dimming	Phase (triac) dimmer, 1-10V, DALI (1-10V and DALI driver are external mounted driver)
Mains connection	Screw terminal connection
Accessories	Honeycomb Anti-Glare Louvre
Materials	Aluminium, plastic
Fire safety	Glow wire test 750°C, UL94V-0, VW-1
Flammability mark	F
IP code	IP20
Safety class	Class 2
Standards	IEC 60598-1, IEC 61347-2-13
Regulatory markings	CCC, CE, RoHs, ETL
Weight	0.6kg (12W) / 1.2kg (17W, 26W)
Dimensions	Ø60 x 140mm / Ø84 x 147mm

FIXTURE			LED MODULE				DRIVER	
Type	Colour	Accessories	LED Power	Beam Angle	Colour Temp	CRI	Dimming	
VEGAZOOM-PM	---	---	---	---	---	---	---	
	WH Matt White	None	12 12W	15Z45 15°-45°	27 2700K	PA ProART	ND Non-Dim	
	MB Matt Black	AGL Anti-Glare Louvre	17 17W	25Z60 25°-60°	30 3000K		PH Phase	
			26 26W		40 4000K		AN 1-10V	
					50 5000K		DA DALI	

example: VEGAZOOM-PM.WH.12.15Z45.30.PA.ND