

SNOOP 3 WALL MOUNT DOWN

OUTDOOR WALL MOUNTED
LUMINAIRE



- Compatible with MR16, 35 and 50 NEST series LED modules
- Colour temperature options: 2700K, 3000K, 3500K, 4000K, 5000K, WARM DIM, flexiK, tuneWHITE™
- Colour rendering index: 85 or 95
- Up to 50,000 hours L80 lamp life with LM80 tested LED chip packages
- Beam pattern options: 10°, 15°, 20°, 35°, 60° (depending on LED module)
- Luminous Flux (lm): 420lm to 950lm (depending on LED module)
- Supplied with non-dimmable or phase/0-10V/DALI dimmable LED driver
- IP66 IK08
- ATePS™ Automated Thermal Protection System
- ComfyEYE, reduced flicker percentage
- X-BEAM, maximising light output ratio with converging optical lens
- Interchangeable LED module system
- Optional linear spread lens, soft lens and honeycomb anti-glare louvre



FIXTURE
COLOUR OPTIONS



Matt Grey RAL7001



Matt Black RAL9011

REFLECTOR
COLOUR OPTIONS



Matt Grey RAL7001



Matt Black RAL9011

tuneWHITE™ and flexiK are recommended to be paired with Soft Lens for better colour mixing effect.

AVAILABLE OPTIONS

LED MODULE



MR16



35N



50N

COLOUR TEMPERATURE



2700K 3000K 3500K 4000K 5000K



ProART



tuneWHITE™



WARM DIM



flexiK

DRIVER



(ND)



(PH)



(AN)



(DA)

ACCESSORIES



Honeycomb
Anti-Glare Louvre




Soft Lens



Linear
Spread Lens


BEAM ANGLE

SINGLE CCT
35 NEST / 50 NEST




10° 20° 35° 60°

WARM DIM
35 NEST / 50 NEST




10° 20° 35° 60°

SINGLE CCT
35 NEST ND+ / 50 NEST ND+




15° 20° 35° 60°

tuneWHITE™ / flexiK
50 NEST



20° 35° 60°

DIMENSIONS (MM)




PHOTOMETRICS


SNOOP 3 WALL MOUNT

50 NEST ND+

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER

	Emax (lx)			
	15°	20°	35°	60°
E (0°)	3734	3744	2202	763
Cone DØ (m)	0.33	0.34	0.60	1.22
E (0°)	933	936	550	191
Cone DØ (m)	0.66	0.68	1.19	2.43
E (0°)	415	416	245	85
Cone DØ (m)	0.99	1.03	1.79	3.65


Correction Factor : 35Nest ND+ - f = 0.67

50 NEST

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER

	Emax (lx)			
	10°	20°	35°	60°
E (0°)	5555	5107	2324	805
Cone DØ (m)	0.19	0.25	0.60	1.22
E (0°)	1389	1277	581	201
Cone DØ (m)	0.37	0.51	1.19	2.43
E (0°)	617	567	258	89
Cone DØ (m)	0.56	0.77	1.79	3.65


Correction Factor : 35N - f = 0.74

50 NEST WARM DIM

POLAR DIAGRAM



CONE DIAGRAM




Ø = DIAMETER

	Emax (lx)			
	10°	20°	35°	60°
E (0°)	4296	2413	1419	491
Cone DØ (m)	0.19	0.34	0.60	1.22
E (0°)	1074	603	355	123
Cone DØ (m)	0.37	0.68	1.19	2.43
E (0°)	477	268	158	55
Cone DØ (m)	0.56	1.03	1.79	3.65


Correction Factor : 35N WD - f = 0.72

50 NEST tuneWHITE™ / flexiK

POLAR DIAGRAM



CONE DIAGRAM



Ø = DIAMETER

	Emax (lx)		
	20°	35°	60°
E (0°)	2496	1468	508
Cone DØ (m)	0.34	0.60	1.22
E (0°)	624	367	127
Cone DØ (m)	0.68	1.19	2.43
E (0°)	277	163	56
Cone DØ (m)	1.03	1.79	3.65

Correction Factor : Coin TWIK - f = 0.60

SNOOP 3 WALL MOUNT

ORDERING MATRIX CHART

FIXTURE						SINGLE CCT LED MODULE				DRIVER
Type	IP	Shape	Colour	Reflector Colour	Accessories	LED Power	Beam Angle	Colour Temp	CRI	Dimming
SNOOP-3WM										
	IP66	D	GR	GR	None	35N	10°	27	Standard	ND
		UD	MB	MB	AGL	50N	20°	30	PA	PH
					SL		35°	35		AN
					LSL		60°	40		DA
								50		
						35N	15°	27	PA	ND+ ^{PRO}
						50N	20°	30		
							35°	35		
							60°			
WARM DIM LED MODULE										DRIVER
						35N	10°	WD	PA	PH
						50N	20°			AN
							35°			DA
							60°			
tuneWHITE™ LED MODULE										DRIVER
						50N	20°	TW18	PA	DA
							35°	TW27		
							60°			
flexiK LED MODULE										DRIVER
						50N	20°	FK##	PA	PH
							35°			AN
							60°			DA

example: SNOOP-3WM.IP66.D.GR.GR.AGL.50N.35.27.PH
 *Custom RAL colour options available.

denotes the first two digits of preferred CCT ranging from 1800K to 6500K by increment of 100K